

**Concrete Slab on Ground
Design and Details**


Scott M. Tarr, P.E. F.A.C.I.
NORTH S. TARR
CONCRETE CONSULTING, P.C.
Guidance to Concrete Solutions
STarr@NorthSTarrConcrete.com

 **Minnesota Concrete Council**
Dedicated to Cast-in-Place Concrete


October 13, 2020

1

Slab Design



and Detailing



2

The slab every owner expects to see ...



“Lab-Crete”



NORTH S. TARR
CONCRETE CONSULTING, P.C.

3



4



5



6

American Concrete Institute
(ACI 360) Definition

Slab Design - The decision-making process of planning, sizing, detailing, and developing specifications preceding construction of slabs on ground.



7

Designer Responsibility: Develop Clear Project Specs...




8


Contractor Responsibility: Follow Project Specifications...



9



10



11




12

Load-Carrying Capacity

- Determining Factors
 - ✓ Slab Thickness
 - ✓ Concrete Strength
 - ✓ Subgrade Modulus (k)


Always remember that increasing slab thickness is the most effective way to increase floor load-carrying capacity.

Assuming Load-Transfer is Achieved at Joints



13


Concrete Slab Thickness



PCA Design Method


Typical Loading Conditions:

- Axle Loads – Lift Trucks
- Post Loads – Rack Storage
- Distributed Loads – Pallets, Boxes, Rolls




14

Axle Load Design



In general, 80 to 85% of total loaded vehicle weight on front axle.
Critical Design Axle Load



15

Information Needed for Axle-Load Design

- From materials, site, and designer
 - Concrete compressive strength
 - Subgrade modulus
 - Safety Factor (SF)
 - Joint conditions – Joint Factor (JF)
- From lift truck specifications
 - Lift truck capacity
 - Vehicle weight (total axle load)
 - Wheel configuration and spacing
 - Tire pressure
 - Wheel contact area

North S Tarr Concrete Consultants, Inc.

16

Design for Maximum Capacity

Why?

“I will only transport one pallet at a time.
I promise...”

North S Tarr Concrete Consultants, Inc.

17

Design for Maximum Capacity



“Just One Pallet!”

North S Tarr Concrete Consultants, Inc.

18



19

Maximum Allowable Bending
~~Concrete Working Stress~~

$$WS = \frac{MR}{SF \times JF}$$

where,
 WS = Working stress
 MR = Modulus of rupture (flexural strength)
 SF = Safety factor
 JF = Joint factor

North S-Tarr
 Concrete Consultants

20

Concrete Working Stress

Concrete Flexural Fatigue Equations

$\log N = 11.737 - 12.077SR$	for $SR \geq 0.55$Eq. 1
$N = \left(\frac{4.2577}{SR - 0.4325} \right)^{3.368}$	for $0.45 < SR < 0.55$Eq. 2
$N = unlimited$	for $SR \leq 0.45$Eq. 3


Where:
 SR = Stress ratio (flexural stress divided by the flexural strength)
 N = Projected number of allowable 16-kip single axle bus load applications to flexural fatigue failure.

North S-Tarr
 Concrete Consultants

21

Joint Factor

- Original PCA Charts developed for interior loading by pneumatic tired wheels
- Stresses due to edge loading are higher - up to 60% higher
- Edge loading occurs at joints that do not have complete load transfer
 - Smooth dowel bars or dowel plates
 - Aggregate interlock decreases when joint opens



22

Joint Factor

Concrete Shrinkage

Table 5-2. Joint Factors Based on Ultimate Concrete Shrinkage*

Ultimate concrete shrinkage, %	Joint factor
<0.052%	1.0
0.052 to 0.057	1.1
0.057 to 0.062	1.2
0.062 to 0.067	1.3
0.067 to 0.072	1.4
0.072 to 0.078	1.5
>0.078	1.6

North S-Tarr Concrete Construction, Inc.

23

Engineering Judgement

- Joint Factor (JF)
- Safety Factor (SF)
- Applied Load Considerations
 - Effective Contact Area
 - Back-to-Back Post Legs
 - Aisle Width v. Load Width


**Complete Set of Design Assumptions
Must Be Considered!**

North S-Tarr Concrete Construction, Inc.


24



25




26



27

Responsibility of the Contractor

Perform Construction Per Specifications And Per Industry Standards




North S-Tarr Concrete Construction, Inc.

28

Jointing

- Joint Types
 - Construction
 - Isolation
 - Contraction/Control



North S-Tarr Concrete Construction, Inc.

29

Construction Joints


- Designate Pour Limits
 - Single Days Placement
- Butt-Type (Formed)
 - Keyways Not Recommended
- Must be Doweled
 - Load Transfer
 - Prevent Differential Movement

North S-Tarr Concrete Construction, Inc.


30



31




32



33




34




Why do Keyways work for Pavement Centerline Joints?
Because they Include Tiebars that Keep the Joint from Widening.

35



Edge Form – Bevel Top and Recess Stakes
Smooth Dowel – Bar or Plate
Cast Slab – Finish Over Edge Form

36



37



38



39



40



41

Contraction Joints

- Control Random Cracking Due To Restraint to Concrete Shrinkage
- Installed at Proper:
 - Spacing
 - Depth
 - Timing


North Star Concrete Council

42

Contraction Joints

Joint - A crack placed where we want it to be.

Crack - A joint placed where the concrete wants it to be.



43

Joints are Generally Preferred




Say No To Crack

44

Contraction Joint Spacing

- American Concrete Institute (ACI)
 - 36 Times Slab Thickness
 - 6-in.-thick slab = 18 ft joint spacing
- Portland Cement Association (PCA)
 - Joint Spacing (ft) = 2 to 2.5 Thickness (in.)
 - 6-in.-thick slab = 12 to 15 ft joint spacing

Maximum 30 Times Slab Thickness
15 ft (4.5 m) Maximum - Pavements



45

Contraction Joint Spacing

ACI
360R

NOTES:

- Joint spacing recommendations based on reducing the curling stresses to minimize shrink-pond cracking (Wichar-Helander 2003). See discussion on Section 5.2 for joint spacing for aggregate interface.
- Joint spacing criteria of 36 and 24 times the slab thickness has been utilized in the past.
- Concrete with an ultimate dry shrinkage strain of less than 720 microstrains placed on a dry base material.
- Concrete with an ultimate dry shrinkage strain of 720 to 780 microstrains placed on a dry base material.
- Concrete with an ultimate dry shrinkage strain of 780 to 1100 microstrains placed on a dry base material.

Fig. 6.6—Recommended joint spacing for unreinforced slabs.

Random
Crack
Control
Only!

46

Contraction Joint Depth

- Create a Weakened Plane to determine Crack Location
 - How Deep? Deep Enough to Cause Crack
 - ¼ Slab Thickness
 6-in.-thick slab = 1½-in.-deep joint
- Grooving/Tooling or Sawcutting
 - Beware of Crack Promoting Insert (Vertical?)

47



48

Contraction Joint Timing

- Before Tensile Stress Exceeds Developed Tensile Strength (Crack)
 - Restraint to Volumetric Decrease
Friction, Penetrations
- Just After Peak Heat of Hydration (Cooling)
 - Drying Shrinkage & Temperature Contraction
 - Generally 8 to 12 Hours After Placement

NORTH STARR
CONCRETE CONSULTING, INC.

49


Joint Reinforcement

- Load Transfer
Transfer load from one panel to the next
 - Aggregate Interlock
 - Mechanical Devices
Dowel Bars
Plate Dowels
 - Transferred Steel Reinforcement

NORTH STARR
CONCRETE CONSULTING, INC.

50

Aggregate Interlock



Minimal Opening Required
< 0.035 in.


Minimize Concrete Shrinkage and Joint Spacing

Be Aware of How Cracks Form in Slabs – “v” Shape

Sawcut Joint Activation

NORTH STARR
CONCRETE CONSULTING, INC.

51



52



53



54



55




56




57




58



59



60



61

Reinforcement Transferred Through Joints

- Welded Wire Fabric (WWF)
 - Mesh - Rolls or Sheets
- Reinforcing Bars
 - Mats
- Post-Tensioning
- Shrinkage-Compensating

North S-Tarr Concrete Solutions


62



63



64




65



66

Transfer Steel Through Joints

- ACI 360
 - <0.1% Steel per Area of Concrete Cross-Section
 - Enhanced Aggregate-Interlock
 - Cracking occurs beneath sawcuts only
 - Joint Spacing per ACI 360R Figure 6.6
 - >0.5% Steel per Area of Concrete Cross-Section
 - Conventionally Reinforced Slab
 - Visible tight cracks expected at 3-5 ft spacing
 - No sawcut joints necessary – no “control”
 - 0.1-0.5% Steel per Area of Concrete Cross-Section
 - “Legalcrete”
 - Visible random cracks that require filling




67

Transfer Steel Through Joints



68


Movement at Sawcut Joints




Sawcut Control Joint

Sawcut Control Joint

69



70




71



72

Post-Tensioned Slabs


Tensioned tendons put slab into permanent compression. Therefore, no tensile stress and associated cracking.



The diagram shows a cross-section of a concrete slab with several tendons embedded within it. Labels include: Fixed End Anchor (Dead End), Sheathing, Tendon, Concrete, Stressing End Anchor (Live End), Bare Tendon for Stressing, Conventional Backup Reinforcing (If Required), and Tendon Access Hole (Formed by a Pocket Former). A small logo for North S-Tarr Concrete Construction is visible in the bottom right corner of the diagram area.

73


Post-Tensioned Slabs



The diagram shows a cross-section of a slab on a base. Labels include: Membrane for Reducing Subgrade Drag, Prestressing Tendon, Construction Joint, Floor Slab, and Base. A small logo for North S-Tarr Concrete Construction is visible in the bottom right corner of the diagram area.

74

Shrinkage-Compensating Slabs



The diagram shows a cross-section of a slab on a base with reinforcement. Labels include: Reinforcement, Floor Slab, and Base. A small logo for North S-Tarr Concrete Construction is visible in the bottom right corner of the diagram area.

Expansive cement or an expansive admixture causes concrete to expand (type K cement).
Steel reinforcement is tensioned and restrains expansion.
Concrete is put into compression – no cracking.

75

Extended-Joint Slab Systems


- Design Extends Joint Spacing Beyond that Recommended by ACI 360.
 - Presumably Assumes No/Minimal Out-of-Joint Random Cracking or Achieves Serviceable Cracking.
 - Owner Should be Informed of Expectation
 - Must Accomplish One or More of the Following:
 - Reduce Concrete Shrinkage Potential to Negligible
 - Reduce Restraint
 - Keep Random Cracks Tight and Closely-Spaced
 - Design for Joint Widening (1/4 the Joints Results in 4 Times the Widening Per Joint)
 - Slab Systems That Require Sawcut Contraction Joints Shrink and Curl.

North S-Tarr Concrete Consultants, Inc.

76

Fiber Reinforcement

- Microsynthetic (0.1% or Less)
 - Monofilament
 - Fibrillated
- Macrosynthetic
 - 0.25 to 1%
- Steel (0.25 to 0.5%)
 - Smooth
 - Deformed



North S-Tarr Concrete Consultants, Inc.

77



78



79



80



81

Concrete Mix Design and Placement Conditions

- ~~High Compressive Strength~~
- ~~Low Water/Cement Ratio~~
- ~~Low Slump~~

Not for Slabs!

- Low Shrinkage Potential
 - ASTM C 157 and ACI 209R
- Good Workability/Finishability
- Required Strength and Durability

NORTH STARR
CONCRETE CONSULTING, LLC

82




83

Concrete Shrinkage/Contraction

- Temperature Contraction
 - 3.2 to 7.5 millionths/°F
 - 1/2 to 1 in. over 100 ft for 100°F change
- Moisture Loss – Volumetric Shrinkage
 - 0.020% to 0.200%
 - 1/4 to 2-1/2 in. in 100 ft

NORTH STARR
CONCRETE CONSULTING, LLC


84




85




86



87




88




89




90



91



92



93



94

Problems with Slab Warping

- Decreased Load-Carrying Capacity Resulting in Long-Term Slab Cracking
 - Mid-Panel Cracks
 - Corner Breaks
- Slab Rocking – Joint Stability

North S-Tarr
Concrete Construction, Inc.


95

Joint Stability

Rocking as Warped Slab Panels are Trafficked

North S-Tarr
Concrete Construction, Inc.


96




97



98



99



100

Joint Spalling

- Stable Joint
- Joint Filler Material
- Wheel Type/Traffic

Two photographs showing joint spalling. The left photo shows a joint with a ruler and a scale. The right photo shows a joint with a wheel and a scale. The text "North Star Concrete" is visible in the bottom right corner.

101

Exterior Pavement Joints

120 psi

Install Flexible Joint Sealant

Install Foam Backer Rod


North Star Concrete

The slide contains a diagram of a wheel on a joint, a cross-section of a joint, and two photographs showing the installation of flexible joint sealant and foam backer rod. The text "120 psi" is visible in the diagram. The text "North Star Concrete" is visible in the bottom right corner.


102



103



104



105

“Minimizing” Shrinkage and Slab Warping

- Use Quality Aggregate
- Minimize Paste Quantity
 - Increase Aggregate Size
 - Optimize Aggregate Gradation
 - Minimize Cement Content
- Maximize Paste Quality
 - Reasonable Water/Cement Ratio
 - Just Enough Water for Workable Slump

North Star Concrete Council

106

ACI 309.1R-16
 Guide to Concrete Floor and Slab Construction
 Reported by Committee 309

8.2—Concrete
 Because minimizing shrinkage is of prime importance, special attention should be given to selecting the best possible concrete mixture proportions. When necessary to determine if a proposed concrete mixture has other than normal shrinkage (ACI 209R), the proposed concrete mixture should be compared with the specified or a reference concrete mixture using ASTM C157/C157M testing, modifying curing, and drying of specimens similar to Caltrans Test 530 (Caltrans 1995). It is essential that the concrete used in these tests be made with the same materials, including admixtures, that will be used in the actual construction.

8.4—Recommended concrete mixture

107

MATERIAL DISTRIBUTION BY SIEVE
 Combined Aggregate Retained

Haystack Curve

~~8-18 Gradation?~~


In general, 5 – 22 percent retained provides workable mix

Blend aggregates to minimize alternating high and low retainage on successive sieves.


Fig. 8.9.4a—Material sieve analysis showing change in aggregate distribution with blending of 3/8 in. (9.5 mm) aggregate.

North Star Concrete Council

108



109



110

Minimizing Water (Paste)

- Use Good Quality Well-Graded Aggregate
- Maximize Coarse Aggregate Topsize to Decrease Total Water in Mix

111



112

Maximum Coarse Aggregate Size

The diagram shows a cross-section of a concrete slab with thickness t . A yellow circle representing a coarse aggregate particle with diameter D_{max} is shown within the slab. To the left, a sieve is shown with aggregate particles of various sizes. Below the diagram, text specifies the maximum aggregate size based on slab thickness and sieve size.

Slab Thickness, t : $D_{max} \leq T/3$
 $D_{max} \leq 3/4 S$

For pumped concrete:
 $D_{max} \leq 1/3$ diameter of hose or
 $\leq 1\frac{1}{2}$ in.
whichever is smaller

North S-Tarr
Concrete Consultants

113


Sieve Analysis ASTM C 136

The image shows a set of sieves used for aggregate analysis, arranged in a pyramid shape. The sieves are labeled with their mesh sizes: #4, #8, #16, #30, #50, and #100. The sieves are placed on a red surface.

Well-Graded
Vs.
Gap-Graded

North S-Tarr
Concrete Consultants

114



115




116

Minimizing Paste Quantity


Balance Between:
Low Shrinkage
and
Workability/Finishability

NORTH STARR
CONCRETE CONSULTING, LLC

117




118




119




120




121




122




123



124



125



126

Slab on Ground Design and Details Conclusions

- Design and build for serviceability in accordance with owners expectations
- Anticipate the drying shrinkage potential for local materials when determining joint reinforcement

Aggregate Interlock

Dowels or Light Reinforcement

Heavy Reinforcement

Post-Tensioned or Shrinkage-Compensated

North S-Tarr
Concrete Council

127

Slab on Ground Design and Details Conclusions

- Design and build for serviceability in accordance with owners expectations
- Anticipate the drying shrinkage potential for local materials when determining joint reinforcement
- Predict the impact of each design and construction feature and advise the owner

Aggregate Interlock

Dowels or Light Reinforcement

Heavy Reinforcement

Post-Tensioned or Shrinkage-Compensated

North S-Tarr
Concrete Council

128



129



130

**Slab on Ground Design and Details
Conclusions**

- Design and build for serviceability in accordance with owners expectations
- Anticipate the drying shrinkage potential for local materials when determining joint reinforcement
- Predict the impact of each design and construction feature and advise the owner
- Always “design” an industrial floor slab. Don’t simply “specify” slabs

North S-Tarr
Concrete Solutions

131



132

Slab on Ground Design and Details Conclusions

- Design and build for serviceability in accordance with owners expectations
- Anticipate the drying shrinkage potential for local materials when determining joint reinforcement
- Predict the impact of each design and construction feature and advise the owner
- Always “design” an industrial floor slab. Don’t simply “specify” slabs
- And remember...

North S Tarr
Concrete Consultants, Inc.

133

Remain Calm!



"STAND BACK - MAKE ONE MORE UNREASONABLE DEADLINE AND I'LL EXPLODE THE DIMENSIONS!"

North S Tarr
Concrete Consultants, Inc.

134



Thank You!
Scott M. Tarr, P.E. FACI
STarr@NorthSTarrConcrete.com

135
