

The **Top 10 Ways** to Reduce Concrete's Carbon Footprint

Donn C. Thompson AIA, LEED AP BD+C
National Ready Mixed Concrete Association





1

AIA Continuing Education – 1 LU/HSW

Learning Objectives

- Understand the basics of embodied carbon in concrete.
- Evaluate the immediate steps that can be taken to reduce carbon footprint when specifying concrete.
- Prioritize design strategies to get the greatest reductions in carbon footprint using current technologies and design tools.
- Explore how innovative technologies will result in zero carbon concrete in the future.



2


Concrete is Unique

Formulation Influenced by:


- Application
- Design professionals
- Contractors
- Specifications

Can be made:

- Stronger
- Weaker
- Lighter
- More flowable
- Stiffer
- Less Permeable



3



4



5



6

Material of Choice

- Thermal mass
- Energy efficiency
- Disaster resilience
- Strength
- Durability

The Challenge

- Offer these benefits
- At lower carbon footprint

7

The Top 10 List

1. Communicate Carbon Reduction Goals
2. Ensure Good Quality Control and Assurance
3. Optimize Concrete Volume
4. Use Alternative Cements
5. Use Supplementary Cementitious Materials
6. Use Admixtures
7. Don't Limit Ingredients
8. Set Targets for Carbon Footprint
9. Sequester Carbon Dioxide in Concrete
10. Encourage Innovation

8

The Top 10 List


1. Communicate Carbon Reduction Goals
2. Ensure Good Quality Control and Assurance
3. Optimize Concrete Volume
4. Use Alternative Cements
5. Use Supplementary Cementitious Materials
6. Use Admixtures
7. Don't Limit Ingredients
8. Set Targets for Carbon Footprint
9. Sequester Carbon Dioxide in Concrete
10. Encourage Innovation

9



No. 1:
**Communicate
Carbon Reduction
Goals**

10




No. 1:
**Communicate
Carbon Reduction
Goals**

1a:
**Collaborate during
design process**

- Meetings and charettes

11



No. 1:
**Communicate
Carbon Reduction
Goals**

**1b. Specify in Part 1
of Concrete Spec**

- This project has a goal of reducing the embodied carbon footprint over a typical project by 30%

12

No. 1:
**Communicate
Carbon Reduction
Goals**

1c. Prebid Meetings

- Re-state the carbon reduction goals and encourage innovation

13



No. 2:
**Ensure Good Quality
Control and Assurance**

14




No. 2:
**Ensure Good Quality
Control and Assurance**


15



16



17




18

Testing Agency Qualifications:

- Meets ASTM C1077
- ACI Concrete Field Testing Technician Grade I
- ACI Concrete Laboratory Testing Technician Level I
- Results certified by a registered design professional

No. 2:
Ensure Good Quality Control and Assurance



19

No. 3:
Optimize Concrete Volume



20



21




Case Study: 960 W. 7th, Los Angeles

- 64-story tower
- 780 residential units
- 807,000 square feet

- Developer: Brookfield Properties
- Design Architect: Marmol Radziner
- Executive Architect: Large Architecture
- Structural Engineer: MKA
- Contractor: Webcor
- Concrete Supplier: National Ready Mixed Concrete Company
- Photos: Brookfield Properties

22



Challenges

- Balancing cost, long term value, energy efficiency, occupant comfort and sustainability
- The design team, developer, contractor and product suppliers have the same goals
- Reducing environmental impact, including carbon footprint.

23




Sustainable Solutions

- Efficient structural system
- Post-tensioned slabs
- Centralized buttressed core
- Optimized floor to floor heights
- Eliminated transfers
- Unobstructed views Performance Based Design
- 80 ksi rebar

24



25



26

ASTM C595		
Type	Description	Notes
Type IL (X)	Portland-Limestone Cement	Where X can be between 5 and 15% limestone
Type IS (X)	Portland-Slag Cement	Where X can be up to 70% slag cement
Type IP (X)	Portland-Pozzolan Cement	Where X can be up to 40% pozzolan (fly ash is the most common)
Type IT (X)(X)	Ternary Blended Cement	Where X can be up to 70% of pozzolan + limestone + slag, with pozzolan being no more than 40% and limestone no more than 15%

**No. 4:
Use Alternative Cements**

27

ASTM C595		
Type	Description	Notes
Type II (X)	Portland-Limestone Cement	Where X can be between 5 and 15% limestone
Type IS (X)	Portland-Slag Cement	Where X can be up to 70% slag cement
Type IP (X)	Portland-Pozzolan Cement	Where X can be up to 40% pozzolan (fly ash is the most common)
Type IT (X)(X)	Ternary Blended Cement	Where X can be up to 70% of pozzolan + limestone + slag, with pozzolan being no more than 40% and limestone no more than 15%

No. 4:
Use Alternative Cements

28

Concrete Materials:

- **Hydraulic Cement:** ASTM C150, ASTM C595, or ASTM C1157

No. 4:
Use Alternative Cements

29

No. 5:
Use Supplementary Cementitious Materials

30


Hydration and SCMs

Portland Cement + Water \rightarrow C-S-H + CH **Hydraulic**

Pozzolan (Fly Ash/Silica Fume) + CH \rightarrow C-S-H **Pozzolanic**

Slag + Water $\xrightarrow[\text{(cement)}]{\text{Alkali/lime Activator}}$ C-S-H (no CH) **Hydraulic**

Slag + CH \rightarrow C-S-H **Pozzolanic**



31



32


NO. 5:
Use Supplementary Cementitious Materials

Concrete Materials:

A. Cementitious Materials: use materials meeting the following requirements:

1. Hydraulic Cement: ASTM C150, ASTM C595, or ASTM C1157
2. Fly Ash or Natural Pozzolan: ASTM C618
3. Slag Cement: ASTM C989
4. Silica Fume: ASTM C1240
5. Glass Pozzolan: ASTM C1866

33



Case Study: UC San Diego, North Torrey Pines Living and Learning Neighborhood

- 10 acres of academic, residential and commercial buildings
- Housing for 2,000 students
- Contractor: Clark Construction
- Architects: HKS in association with Safdie Rabines Architects
- Concrete Specialists: CalPortland Photo: Courtesy of Walter Kanzler

34



Challenges

- University's sustainability policy
- Minimum LEED Silver
- Recommended LEED Gold
- Set to achieve LEED Platinum


35

Cement Type	Global Warming Potential
Portland Limestone Cement Type II (13)	871 kg CO ₂ eq
Portland Cement Type I/II/V	969 kg CO ₂ eq

Sustainable Solutions

- Life Cycle Analyses (LCAs)
- Demonstrate sustainable design and outcomes
- Used Type II blended portland-limestone cement
- Save 3,055 metric tonnes of CO₂

36




37



38



39



40

Concrete Materials:

Chemical Admixtures:

1. Air-Entraining Admixture:
ASTM C 260/C 260M
2. Water-Reducing Admixture
ASTM C 494/C 494M Type A
3. High-Range Water-Reducing
Admixture: ASTM C 494/C 494M
Type F or G
4. Accelerating Admixture:
ASTM C 494/C 494M Type C or E
5. Retarding Admixture: ASTM C 494/
C 494M Type B or D
6. Hydration Control Admixture:
ASTM C 494/C 494M Type B or D

No. 6:

Use Admixtures

41

No. 7:

**Don't Limit
Ingredients**

42

No. 7:
Don't Limit Ingredients

- ^ **Maximum w/cm ratio**
- ^ **Air content of 6% for all concrete**
- ^ **Maximum cement content**
- ^ **Minimum cement content**
- ^ **Maximum fly ash content**
- ^ **Minimum fly ash content**
- ^ **Water: Potable**

43

No. 7:
Don't Limit Ingredients

- ^ **Maximum w/cm ratio**
- ^ **Air content of 6% for all concrete**
- ^ **Maximum cement content**
- ^ **Minimum cement content**
- ^ **Maximum fly ash content**
- ^ **Minimum fly ash content**
- ^ **Water: Potable**

44


No. 7:
Don't Limit Ingredients

Class	Location	Nominal Max. Aggregate Size	Exposure Class	F _c , Psi @ Age
1	Mat Foundation	3"	F0, S1, W0, C0	6,000 at 90 days
2	Basement Walls	1-1/2"	F0, S1, W0, C0	4,000 at 56 days
3	Shear Walls	3/4"	F0, S0, W0, C0	6,000 at 56 days
4	Columns Level B2-L6	3/4"	F0, S0, W0, C0	6,000 at 28 days
5	Columns Level L7-L12	3/4"	F0, S0, W0, C0	4,000 at 28 days
6	Slabs	3/4"	F0, S0, W0, C0	5,000 at 28 days
7	Exterior Pavements	3/4"	F3, S1, W0, C0	4,000 at 28 days


45



46



47




48



49



50



51



52

Impact Measure	Units	Estimated % Reduction from Baseline to Proposed
Acidification Potential	kg SO ₂ eq	-13%
Eutrophication Potential	kg Neq	-3%
Global Warming Potential	kg CO ₂ eq	-12%
Ozone Depletion Potential	CFC-11eq	-11%
Smog Formation Potential	kg O ₃ eq	-12%
Non-Renewable Energy	MJ	-6%

Sustainable Solutions

- Optimized mix designs
- High volume of SCMs
- Test age for drilled piers at 56 days
- Met LEED WBLCA requirement
- At least 10% reduction of GWP (12% in this case)
- At least 10% reduction in at least two other categories

53



54



55

Concrete Materials:

- A. Normal-weight Aggregate: ASTM C33
- B. Lightweight Aggregate: ASTM C330
- C. Recycled concrete aggregate (crushed concrete) meeting the requirements of ASTM C33 or ASTM C330 may be used in structural concrete up to 10% of the total aggregate. Crushed concrete shall have been crushed and exposed to air at least 1 year before use in concrete (to maximize CO2 sequestration).

56

Concrete Materials:

- D. Artificial limestone aggregate meeting the requirements of ASTM C33 or ASTM C330 is permitted.
- E. Carbon mineralization by injecting CO2 into concrete during manufacturing or curing in CO2 atmosphere shall be permitted.

57



58




59



60

Thank you


Donn C. Thompson, AIA, LEED AP BD+C
 National Ready Mixed Concrete Association
 Kenosha, WI
dthompson@nrmca.org 224.627.3933



Free Collaboration Design/Construction Team:

- Structural system recommendations
- First and operating cost comparisons
- Specification review

www.buildwithstrength.com/design-center

BUILD WITH STRENGTH 

61

The Top 10 Ways to Reduce Concrete's Carbon Footprint

Margaret Mills
 Administrator
 Minnesota Concrete Council

P.O. Box 116
 Rosemount, MN 55068

Margaret@mnconcretecouncil.com
 (952) 595-6166



62